



“Pen type” Leeb hardness tester for mobile hardness testing of metals

Features

- **User-friendly operation:** The compact version enables the product to be used in a significantly wider range of applications compared with traditional devices
- The measuring device has been designed for one-hand operation and this allows the user to work more quickly and flexibly
- **Modern LCD display:** Optimised for industrial applications: increased luminosity and backlight can be switched on, that way the display can be read from any angle
- **All measurement directions possible (360°)** thanks to an automatic compensation function
- **Internal impact sensor** included (Type D)
- **Measurement value display:** Rockwell (B & C), Vickers (HV), Brinell (HB), Shore (HSD), Leeb (HL)
- **Hardness comparison block** not included
- **Internal data memory** for up to 500 measurements with date and time
- **USB-PC data output:** Easy to install on any PC
-  Delivered in a hard carrying case

Technical data

- Accuracy ± 4 HLD
- Dimensions WxDxH 35x25x145 mm
- Operation by rechargeable battery pack, standard
- Mains adapter, external, standard
- Net weight approx. 0,07 kg

Accessories

- **PC software to download stored data**, for statistical evaluation, and transfer to Microsoft Excel, SAUTER AHN-01
-  **Attachment rings** for secure positioning, SAUTER AHMR 01
-  **Test block** Type D/DC, $\varnothing$ 90 mm (± 1 mm), Net weight < 3 kg, hardness range 790 $\pm$ 40 HL, SAUTER AHMO D02 630 $\pm$ 40 HL, SAUTER AHMO D03 530 $\pm$ 40 HL, SAUTER AHMO D04
- **ISO calibration certificate** for SAUTER AHMO D02, AHMO D03, AHMO D04, SAUTER 961-132
-  **Thermal printer**, wireless infrared connection to SAUTER HN-D, HMM, HMO, SAUTER AHN-02
- **Paper roll**, 1 piece, for SAUTER AHN-02, SAUTER ATU-US11

STANDARD



OPTION



Model	Sensor	Measuring range	Readout		Option	
					ISO Calibration Certificate	
SAUTER		[Max]	[d]		ISO	
HN-D.	Type D	0 - 999	1		KERN	
					961-131	



Adjusting program (CAL):
For quick setting of the balance's accuracy.
External adjusting weight required.



Data interface Infrared:
To transfer data from the balance to a printer, PC or other peripheral devices.



Battery operation:
Ready for battery operation.
The battery type is specified for each device.



Calibration block:
standard for adjusting or correcting the measuring device.



Control outputs (optocoupler, digital I/O):
to connect relays, signal lamps, valves, etc.



Rechargeable battery pack:
rechargeable set.



Peak hold function:
capturing a peak value within a measuring process.



Analogue interface:
to connect a suitable peripheral device for analogue processing of the measurements.



Mains adapter:
230V/50Hz in standard version for EU.
On request GB, AUS or USA version available.



Scan mode:
continuous capture and display of measurements.



Statistics:
using the saved values, the device calculates statistical data, such as average value, standard deviation etc.



Power supply:
Integrated, 230V/50Hz in EU.
More standards e.g. GB, AUS or USA on request.



Push and Pull:
the measuring device can capture tension and compression forces.



PC Software:
to transfer the measurements from the device to a PC.



Motorised drive:
The mechanical movement is carried out by a motorised drive.



Length measurement:
captures the geometric dimensions of a test object or the movement during a test process.



Printer:
a printer can be connected to the device to print out the measurements.



Fast-Move:
the total length of travel can be covered by a single lever movement.



Focus function:
increases the measuring accuracy of a device within a defined measuring range.



GLP/ISO record keeping:
of measurements with date, time and serial number. Only with SAUTER printers.



ISO Calibration:
The time required for ISO calibration is shown in days in the pictogram.



Internal memory:
to save measurements in the device memory.



Measuring units:
Weighing units can be switched to e.g. non-metric at the touch of a key.
Please refer to website for more details.



Package shipment:
The time required for internal shipping preparations is shown in days in the pictogram.



Data interface RS-232:
bidirectional, for connection of printer and PC.



Measuring with tolerance range:
Upper and lower limiting can be programmed individually, e.g. for sorting and dosing.



Pallet shipment:
The time required for internal shipping preparations is shown in days in the pictogram.



Data interface USB:
To connect the balance to a printer, PC or other peripheral devices.



ZERO:
Resets the display to "0".



Warranty:
The warranty period is shown in the pictogram.

Your SAUTER specialist dealer:

Elastocon®

Tvinnargatan 25 • SE-507 30 Brämhult
Tfn: 033-22 56 30 • Fax: 033-13 88 71
info@elastocon.se • www.elastocon.se